

OPTIMA
Oberflächentechnik
BEFRAG



OPTIMA 2100

Professional Air Combi Paint Spray Gun

strong. innovative. precise.

OPTIMA 2100

Air Combi

OPTIMA
Oberflächentechnik
BEFRAG

Order-No: 1248



- Excellent atomization and finish due to unique Injector-Technology
- Every standard nozzle size equipped with matching pre-atomization nozzle
- Unique separate round and flat jet regulation ensures optimal adjustment possibilities
- Outstanding low trigger force eliminates arm fatigue
- Adjustable paint spring pressure from 80 – 250 bar
- Easy removal of complete paint needle from the rear
- Convenient external adjustable needle sealing
- Ball bearing swivel joint at the paint connection
- Swivel joint at the air connection
- High quality aluminum safety bar
- Elegant streamline surface ensures easy surface cleaning
- Handy lightweight design with optimum center of gravity ensures ergonomic handling and user comfort
- Extensive nozzle and filter models available
- Easy maintenance

Technical Data:

- Material pressure: up to 250 bar
- Air consumption (at 2.5 bar): 220 liter/min
- Transfer efficiency: ca. 85%
- Weight: 598 g (incl. paint filter and swivel joint)
- Available nozzle sizes: Spray angle: 20° - 90°, Nozzle sizes: 0.18 – 1.16
- Available filter inserts: 50 µm, 100 µm (standard), 150 µm